



MACJAMES®MRWL-07 - RIG WASH LIQUID

PRODUCT TECHNICAL DATA SHEET

PRODUCT DESCRIPTION

MACJAMES®MRWL-07 - RIG WASH LIQUID/INDUSTRIAL DETERGENT

(DPR/HSE.04/003.700/2019/004 and ISO 9001:2015 Cert. No.: N1683535) is an innovative and economical industrial detergent with emulsifying concentrated strength to clean dirt from many surfaces where ordinary detergents limitations end. It cleanses grease, oil, bitumen residue, mud, carbon deposits, grime, slag, etc from the various surfaces. Its alkalinity and flowability (low viscosity) make it easy to spread and penetrate into the heavy dirt to break their bonds for easy rinse off. It is blendable with hard/soft, salt/fresh, hot/cold water media. It is biodegradable, non-solvent based, non-toxic, environmentally friendly and non-corrosive chemical industrial liquid detergent. **It solves the problems of cleaning heavy and tough industrial dirt/soil where ordinary detergents cannot be a solution.** It could be used in hand, power and steam washing activities in appropriate ratio to water in these areas:

- Drilling rig and platforms
- Petrochemical and refineries, etc.
- Vessels and silos
- Workshop and machine parts
- Marine and dredging equipment
- Production and factory floors
- Farm and construction equipment
- Heavy soiled equipment and surfaces.

PACKAGING SIZES: 4 Litres : 20 Litres : 25 Litres : 200 Litres drum and IBC Tank (1,000 Litres). Others on request.

INNOVATIVE FEATURES

- *Safe on surfaces*
- *Biodegradable*
- *Non-toxic*
- *Emulsifying*
- *High foaming*
- *Low Viscosity*
- *Non-acidic*
- *Non-flammable*
- *Non-solvent based*
- *100% Water Soluble*

BENEFITS

- ✓ *Highly economical*
- ✓ *Not destructive to metals and non metals*
- ✓ *Full industrial strength*
- ✓ *Removes organic and inorganic soils*
- ✓ *Safe to users*
- ✓ *Effective in soft and hard water*
- ✓ *Blendable with hot water and solvents for special degreasing jobs*





APPLICATION INFORMATION:

SURFACES/SUBSTRATES OF APPLICATION:

Platforms and oilfield equipment, machine parts, soiled engines, fouled heat exchangers, workshop/factory floors, storage tanks/reservoirs, marine and dredging equipment, rigs and superstructures and other soiled surfaces or equipment.

DIRECTIONS FOR USE:

- ❖ Use on all washable water-safe surfaces only.
- ❖ Spray, apply with brush, or soak soiled surfaces and substrates.
- ❖ Allow solution to penetrate for 2 - 5 minutes, depending on soil level.
- ❖ Scouring or Scrubbing or high-pressure application is recommended to remove stubborn deposits.
- ❖ Rinse or flush with clean water until surface is free from dirt and detergent.

DILUTION RATIOS:

HEAVY SOIL: Use full strength concentration.

MEDIUM SOIL: Use 1:5 parts water to 1:20 parts water dilute solution.

LIGHT CLEANING: Use 1:20 parts water to 1:100 parts water dilute solution.

IN THE RIGHT DILUTION, POWER OR PRESSURE WASH CAN BE USED ON SURFACES AND INACCESSIBLE SOILED AREAS.

- ❖ Rinsing: High pressure hot water is more effective for inaccessible areas.

MACJAMES® MRWL-07 - RIG WASH LIQUID is known to be environmentally friendly, non-toxic and safe for general health but commonsense precautions are recommended.

PRECAUTIONS

- KEEP AWAY FROM CHILDREN
- Use hand gloves during application.
- Do not drink.
- Avoid contact with eyes or skin, otherwise flush with plenty water.
- Wash hands with water after using chemicals.
- If swallowed, drink water and see a doctor.
- Dilute with plenty water before disposal.

INGREDIENTS: It is manufactured from De-ionized water, ionic and other surfactants, preservative, etc.



HAZARDOUS MATERIALS IDENTIFICATION SYSTEM (HMIS) RATING:

HEALTH	0	0 - Minimal
FLAMMABILITY	0	1 - Slight
PHYSICAL HAZARD	0	2 - Moderate
PERSONAL PROTECTION	B	3 - High
		4 - Very High

NB: The Material Safety Data Sheet (MSDS) of **MACJAMES® MRWL-07 - RIG WASH LIQUID** is readily available for more information or contact us at info@macjamesglobal.com.

PHYSICAL PROPERTIES

PHYSICAL PROPERTIES			
Appearance:	Light cream to colourless	Foaming Tendency:	High
Odour:	Industrial detergent	Concentration Monitoring Techniques:	Titration
Specific Gravity @ 20°C :	1.02	Water solubility:	Complete
Viscosity:	Low	Rinsability:	Excellent
pH:	8.0 - 11	Flash Point:	none
Freezing Point:	Approx. -5°C	Boiling Point:	Approx. 100 °C



TYPICAL PHOTOS: SIZES AND PACKAGED FOR DELIVERY OF MACJAMES® MRWL-07 - RIG WASH LIQUID



NON-WARRANTY – All data, statements and recommendations contained herein are based upon the best information available and are believed to be reliable. However, no warranty, either expressed or implied, is made concerning the application of this product since the customer’s use cannot be controlled directly by Macjames.

